


# Yealink

## #1 SIP PHONE IN SA

The preferred partner for all your VoIP, VC and Unified Communication Requirements



Crystal Clear  
Communication,  
a Phone Call Away



Video  
Collaboration,  
Made Easy



Conference  
Calling,  
Simple & Effective



Official Yealink Platinum Distributor



3 YEAR WARRANTY

MODEL:	T58A	T56A	T49G	T48S	T46S	T42S	T41S	T40P/G
<b>DISPLAY</b>								
LCD Display	7" 1024x600 Pixel, Colour Touch LCD Display	7" 1024x600 Pixel, Colour Touch LCD Display	8" 1280x800 Pixel, Colour Touch LCD IPS Display	7" 800x480 Pixel, Colour Touch LCD Display	4.3" 480x272 Pixel, Colour LCD Display	2.7" 192x64 Pixel, LCD Display	2.7" 192x64 Pixel, LCD Display	2.3" 132x64 Pixel, LCD Display
LCD Backlight	•	•	•	•	•	•	•	•
Android	•	•						
<b>HARDWARE</b>								
Line Keys					10	6	6	3
Memory Keys	27 (3-page-view)	27 (3-page-view)	29	29	27 (3-page-view)	15 (3-page-view)	15 (3-page-view)	4
Wall Mount	Optional	Optional		•	•	•	•	•
Voltage Rating	5V/2A	5V/2A	12V/2A	5V/2A	5V/2A	5V/1.2A	5V/1.2A	5V/600mA
Expansion Module Support	•	•		•	•			
<b>AUDIO FEATURES</b>								
HD Voice	•	•	•	•	•	•	•	•
Wideband Codec	Opus, G.722	Opus, G.722	Opus, G.722	Opus, G.722	Opus, G.722	Opus, G.722	Opus, G.722	Opus, G.722
Narrowband Codec	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, G.722.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, G.722.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus (T40G only), G.711µ/A, G.729A/B, G.726
Speakerphone	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex	Full Duplex
<b>INTERFACE</b>								
Ethernet Ports	2	2	2	2	2	2	2	2
Ethernet Interface	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100 Mbps	10/100 Mbps (T40P) 10/100/1000 Mbps (T40G)
PoE Support	Yes	Yes	No	Yes	Yes	Yes	Yes	Yes
Headset Support	(USB Headset Support)	(USB Headset Support)	•	•	•	•	•	•
<b>TELEPHONE FEATURES</b>								
SIP Accounts	16	16	16	16	16	12	6	3
Conferencing (with terminal)	5 parties <i>(multi-party dependent on server)</i>	5 parties <i>(multi-party dependent on server)</i>	3 Way Video Conferencing	3 parties <i>(multi-party dependent on server)</i>	3 parties <i>(multi-party dependent on server)</i>	3 parties <i>(multi-party dependent on server)</i>	3 parties <i>(multi-party dependent on server)</i>	3 parties <i>(multi-party dependent on server)</i>
Speed Dial	•	•	•	•	•	•	•	•
BLF	•	•	•	•	•	•	•	•
BLA	•	•	•	•	•	•	•	•
Call Transfer	•	•	•	•	•	•	•	•
Call Forward	•	•	•	•	•	•	•	•
Call Waiting	•	•	•	•	•	•	•	•
XML Browser	•	•	•	•	•	•	•	•
Local Phonebook	1000 Entries	1000 Entries	1000 Entries	1000 Entries	1000 Entries	1000 Entries	1000 Entries	1000 Entries
XML Phonebook	•	•	•	•	•	•	•	•
LDAP Phonebook	•	•	•	•	•	•	•	•
<b>SECURITY &amp; CONFIGURATION</b>								
SRTP/TLS/HTTPS	•	•	•	•	•	•	•	•
OpenVPN	•	•	•	•	•	•	•	•
Auto Provisioning	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS
<b>ACCESSORIES (OPTIONAL)</b>								
Expansion Module	EXP50	EXP50		EXP40	EXP40			
Power Adapter	PSU-COLOUR	PSU-COLOUR	PSU-COLOUR	PSU-COLOUR	PSU-COLOUR	PSU-MONO	PSU-MONO	PSU-MONO
Headset	YHS33 & YHS33-USB	YHS33 & YHS33-USB	YHS33	YHS33 & YHS33-USB	YHS33 & YHS33-USB	YHS33 & YHS33-USB	YHS33 & YHS33-USB	YHS33
Bluetooth USB Dongle	Built-in	Built-in	Built-in	BT40	BT40	BT40	BT40	BT40
Wi-Fi USB Dongle	Built-in	Built-in	Built-in	WF40	WF40	WF40	WF40	WF40
Camera	CAM50							
DECT Support						DD10K	DD10K	

# Yealink

## IP DESKTOP PHONES



2 YEAR WARRANTY

MODEL:	T29G	T27G	T23G	T21P E2
<b>DISPLAY</b>				
LCD Display	4.3" 480x272 Pixel, Colour LCD Display	3.66" 240x120 Pixel, LCD Display	2.8" 132x64 Pixel, LCD Display	2.3" 132x64 Pixel, LCD Display
LCD Backlight	•	•	•	•
<b>HARDWARE</b>				
Line Keys	10	8	3	2
Memory Keys	27 (3-page-view)	21 (7 keys of 3 pages)		
Wall Mount	•	Optional	•	•
Voltage Rating	5V/2A	5V/1.2A	5V/1.2A	5V/600mA
Expansion Module Support	•	•		
<b>AUDIO FEATURES</b>				
HD Voice	•	•	•	•
Wideband Codec	G.722	Opus, G.722	G.722	G.722
Narrowband Codec	G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	Opus, G.711µ/A, G.729A/B, G.726, iLBC	G.711µ/A, G.729A/B, G.726, iLBC	G.711µ/A, G.729A/B, G.726, iLBC
Speakerphone	Full Duplex	Full Duplex	Full Duplex	Full Duplex
<b>INTERFACE</b>				
Ethernet Ports	2	2	2	2
Ethernet Interface	10/100/1000 Mbps	10/100/1000 Mbps	10/100/1000 Mbps	10/100 Mbps
PoE Support	Yes	Yes	Yes	Yes (Excl. T21 E2)
Headset Support	•	•	•	•
<b>TELEPHONE FEATURES</b>				
SIP Accounts	16	6	3	2
Conferencing (with terminal)	3 parties (multi-party dependent on server)	3 parties (multi-party dependent on server)	3 parties (multi-party dependent on server)	3 parties (multi-party dependent on server)
Speed Dial	•	•	•	•
BLF	•	•	•	•
BLA	•	•	•	•
Call Transfer	•	•	•	•
Call Forward	•	•	•	•
Call Waiting	•	•	•	•
XML Browser	•	•	•	•
Local Phonebook	1000 Entries	1000 Entries	1000 Entries	1000 Entries
XML Phonebook	•	•	•	•
LDAP Phonebook	•	•	•	•
<b>SECURITY &amp; CONFIGURATION</b>				
SRTP/TLS/HTTPS	•	•	•	•
OpenVPN	•	•	•	•
Auto Provisioning	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS
<b>ACCESSORIES (OPTIONAL)</b>				
Expansion Module	EXP20	EXP20		
Power Adapter	PSU-COLOUR	PSU-MONO	PSU-MONO	PSU-MONO
Headset	YHS33	YHS33	YHS33	YHS33
Bluetooth USB Dongle	BT40	BT40		
Wi-Fi USB Dongle	WF40	WF40		

# Yealink

## IP DECT PHONES



2 YEAR WARRANTY

MODEL:	W52P	W53P	W60P
<b>DISPLAY</b>			
LCD Display	1.8" 128x160 Pixel Colour LCD Display	1.8" 128x160 Pixel Colour LCD Display	2.4" 240x320 Pixel Colour LCD Display
LCD Backlight	•	•	•
<b>HARDWARE</b>			
Wall Mount	•	•	•
Voltage Rating	5V600mA	5V600mA	5V600mA
<b>AUDIO FEATURES</b>			
HD Voice	•	•	•
Wideband Codec	G.722	Opus, AMR-WB (optional), G.722	G.722
Narrowband Codec	G.711µ/A, G.729A/B, G.726, G.723.1, iLBC	PCMU, PCMA, G.726, G.729, iLBC	G.711µ/A, G.729A/B, G.726, G.723.1, iLBC
Speakerphone	Full Duplex	Full Duplex	Full Duplex
<b>INTERFACE</b>			
Ethernet Ports	1	1	1
Ethernet Interface	10/100Mbps	10/100Mbps	10/100 Mbps
PoE Support	•	•	•
Headset Support	2.5mm	3.5mm	3.5mm
<b>TELEPHONE FEATURES</b>			
SIP Accounts	5 (4 simultaneous calls)	8 (8 simultaneous calls)	8 (8 simultaneous calls)
Conferencing (with terminal)	3 parties (multi-party dependent on server)	3 parties (multi-party dependent on server)	3 parties (multi-party dependent on server)
Speed Dial	•	•	•
Call Transfer	•	•	•
Call Forward	•	•	•
Call Waiting	•	•	•
Local Phonebook	500 Entries	800 Entries	500 Entries
Range	50M Indoors, 300M Outdoors	50M Indoors, 300M Outdoors	50M Indoors, 300M Outdoors
Talk Time	5-10 Hours, 100 Hours Standby	18 Hours, 200 Hours Standby	30 Hours, 400 Hours Standby
USB Quick Charge		•	•
<b>SECURITY &amp; CONFIGURATION</b>			
SRTP/TLS/HTTPS	•	•	•
OpenVPN	•	•	•
Auto Provisioning	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS	FTP/TFTP/HTTP/HTTPS
<b>ACCESSORIES (OPTIONAL)</b>			
DECT Repeater RT30	•	•	•
Additional Handset	W52H	W53H	W56H

# Yealink

## IP CONFERENCE PHONES



2 YEAR WARRANTY

MODEL:	CP920	CP930W	CP960
<b>DISPLAY</b>			
LCD Display	3.1" 248x120 Pixel, LCD Display	3.1" 248x120 Pixel, LCD Display	5" 720x1280 Pixel, Colour, Touch LCD
LCD Backlight	•	•	•
<b>HARDWARE</b>			
Soft Keys	4	4	N/A
Voltage Rating	DC12V/1A	DC12V/1A	PoE, YLPOE30 (Optional)
<b>AUDIO FEATURES</b>			
Microphone Array	3	3	3
Voice Pickup	360 Degree	360 Degree	360 Degree
Speaker	5W	5W	10W
Echo Cancellation	Up to 320ms Tail Length	Up to 240ms Tail Length	Up to 320ms Tail Length
Noise	Yealink Noise Proof Technology	Yealink Noise Proof Technology	Yealink Noise Proof Technology
<b>INTERFACE</b>			
Ethernet Interface	10/100 Mbps	N/A	10/100 Mbps
PoE Support	•	N/A	•
Microphone Ports	N/A	N/A	2 x External Mic Ports
USB	1 x USB2.0	1 x Mic Port	2 x USB2.0, 1 x USB2.0 Micro-B
Mobile Phone / PC Port	N/A	N/A	1 x 3.5mm Jack
<b>FEATURES</b>			
Android	N/A	N/A	•
HD Voice	•	•	•
Wi-Fi Support	Built-In	N/A	Built-In
Bluetooth Support	Built-In	Built-In	Built-In
Speakerphone	Full Duplex	Full Duplex	Full Duplex
Microphone Expansion Modules	N/A	N/A	Optional
Conferencing Support	5 Way	5 Way	5 Way
Recording	USB Call Recording	Micro SD Card Recording	USB or Local (up to 100 hours local)
SIP Accounts	1	N/A	1
Cordless	N/A	•	N/A
<b>ACCESSORIES (OPTIONAL)</b>			
Wireless Microphones CPW90	N/A	N/A	Optional
Wired Microphones CPE90	N/A	N/A	Optional
PoE Adapter YLPOE30	Optional	N/A	Optional
DECT Base Station W60B	N/A	Optional	N/A

# Yealink

## EXPANSION MODULES



2 YEAR WARRANTY

MODEL:	EXP50	EXP40	EXP20
<b>DISPLAY</b>			
LCD Display	4.3" 480x272 Pixel, Colour LCD Display	160x320 Pixel LCD	160x320
LCD Backlight	•	•	•
Two Page Views	•	•	•
<b>FEATURE KEYS &amp; INDICATORS</b>			
Physical Keys	20	20	20
Dual Colour LEDs	•	•	•
Extensions	40	40	38
Independent Switch Key	•	•	
All Keys Programmable	Shared Line, BLF List, Call Park, etc.	Shared Line, BLF List, Call Park, etc.	Shared Line, BLF List, Call Park, etc.
<b>PHYSICAL FEATURES</b>			
Wall Mountable		•	
Stand	2 Adjustable Angles	2 Adjustable Angles	2 Adjustable Angles
Powered by Phone	1 Module	Up to 2 Modules	Up to 2 Modules
Max. Modules in Daisy Chain	3 (2 with independent power)	6 (4 with independent power)	6 (4 with independent power)
Phone Models Supported	T58A & T56A	T48S & T46S	T29G & T27G

## Technology Partners:

